

Tanaka Sleeper and Bonding Drills

Tanaka TED270-RS Sleeper Drill



Part No. 1540116

Bonding Drill



Part No. FP-112-43

Specifications

Engine	Tanaka 2-Stroke Full Crank
Displacement (cc)	27.0
Max hp	1.5
Max kW	1.1
Handle Type/s: Front	2-Position Adjustable (L or R)
Rear	Pistol Grip
Clutch System	Centrifugal
Starter System	Recoil - SmartStart
SmartStart	Standard
Ignition	Electronic
Carburettor	Walbro Diaphragm with Primer Assist
Muffler System	Spark Arrestor
Reduction Ratio	20:1
Chuck Size (mm/in)	12.5 / 1/2" (Standard)
Max Chuck RPM at Engine RPM	0-450 / 9000
Maximum Drill Bit	1 1/2" (Soft Wood) 1" (Hard Wood)
Fuel Tank Capacity (cc)	500
Weight (kg)	5.0
Optional Attachments:	Tree Planting Bit
See Accessories	Keyed Chuck

- 1.5hp Two-Stroke Engine features
- SmartStart Recoil - 50% less force required to start
- Two Piston Rings and a Stress Relieved, Chrome-plated Cylinder for
- Longer engine life
- Dual Position Front Handle - Left or Right for Operator Flexibility
- Portable and light-weight
- Drill anywhere - in any position - without the hassles of electrical cords, compressors, generators or battery rechargers
- Lever Activated Powered Reversing Feature
- ½ Inch Keyless Chuck accepts
- A wide variety of Wood, Steel, and Concrete bits
- No nonsense 2-stroke maintenance -
- Designed and Manufactured by Japan's Finest Engineers
- Security and peace of mind with
- Comprehensive Spare Parts Range available
- Tanaka Warranty provides
- One-Year Coverage for Professionals
- Five-Year Coverage for Homeowners